

GALVANIC ISOLATOR

- To avoid offset current between different electrical potentials
- Capacitors for galvanic isolation of IN- and outputs
- Immunity to surge voltages up to 1 kV
- No DELTA Electronics labelling



| Type | | TRISX-1002 |
|----------------------------|-----|---------------------------------------|
| Item No. | | 57004079 |
| Frequency range | MHz | 5 - 1218 |
| Through loss | dB | 0.4 ... 0.7 |
| Linearity | dB | ± 0.5 |
| Immunity to surge voltages | kV | 1 (between in- and output potentials) |
| Dimensions | mm | 60 x 30 x 38 |

TRIS HOUSING

- TRIS-housing for the galvanic isolator
- Suitable for TRIS-1002 AEN & TRISX-1002



| Type | | TRIS-Housing |
|------------|----|--------------|
| Item No. | | 57001201 |
| Dimensions | mm | 85 x 85 x 40 |

FIX ATTENUATOR

- Small housing, 40 x Ø 11 mm
- Connector: F-female and F-male
- CLASS A



| Type | FR 3-3 | FR 3-6 | FR 3-10 |
|-----------------|----------|----------|----------|
| Item No. | 57001154 | 57001155 | 57001156 |
| Frequency range | MHz | 5 - 2400 | 5 - 2400 |
| Attenuation | dB | 3 | 6 |
| Remarks | | DC-Pass | DC-Pass |

| Type | FR 1-3 | FR 1-6 | FR 1-10 |
|-----------------|----------|----------|----------|
| Item No. | 57002351 | 57002352 | 57002353 |
| Frequency range | MHz | 5 - 1218 | 5 - 1218 |
| Attenuation | dB | 3 | 6 |