

TWIN-WALL OUTLET SAT-IF

- Twin-wall outlet for 2-wire-SAT-IF application
- With DC pass
- Including cover plate and frame



Type	Frequency range		STD 2400
Item No.			10161174
Description			Terminal-twin wall outlet
Attenuation			
TV OUT (IEC-male)	dB	85-862 MHz	1.0 - 2.0
RF OUT (IEC-female)	dB	87.5-862 MHz	1.0 - 2.0
2x SAT OUT (F-female)	dB	950-2200 MHz	4.0 - 6.5
DC pass			12 V = max. 500 mA (over SAT-IF-connectors)

ACCESSOIRES FOR ANTENNA WALL OUTLETS

Type	AD 3 SET		AD 3-2	AP 1
Item No.	57001452		57004041	10161348
Description	Set with cover plate (2 parts) and frame for 3-hole outlets (pure white)		cover plate 2 part for 3-hole outlets (pure white)	Frame (pure white)
Dimensions	mm	76 x 76 x 8 / 76 x 76 x 32	76 x 76 x 8	76 x 76 x 32

Type	R 75		R 75 DC
Item No.	57000813		57000990
Description	Terminal resistor		Terminal resistor DC isolated
Frequency range	MHz	0 – 2200	10 – 2200
Load		75 Ohm	75 Ohm
Application		For DC isolated walloutlets	For SAT-wall outlets with DC pass