

# HOUSE AMPLIFIER PROFI-LINE BKE-PS

- BKE-PS amplifier: return way on board
- Precise and reliable adjustments by variable level attn. (PS) for level and slope control
- Low noise
- LED indicator for operation status
- Vodafone Kabel Deutschland GmbH certified



## Types: BKE-PS

Type	BKE 22 PS-KDG	BKE 33 PS-KDG	BKE 36 PS-KDG	BKE 39 PS-KDG
Item No.	57002408 (PU:10) 57002595 (PU:1)	57002409 (PU:10) 57002596 (PU:1)	57002410 (PU:10) 57002597 (PU:1)	57002411 (PU:10) 57002598 (PU:1)
Description	Amplifier with level attn.	Amplifier with level attn.	Amplifier with level attn.	Amplifier with level attn.
Frequency range US / DS	MHz 5-65 / 85-1006	MHz 5-65 / 85-1006	MHz 5-65 / 85-1006	MHz 5-65 / 85-1006
Gain US / DS	dB 18 / 20	dB 25 / 33	dB 25 / 35	dB 29 / 39
Adjustment level / slope DS	dB 0 ... 20	dB 0 ... 20	dB 0 ... 20	dB 0 ... 20
Interstage slope DS (Jumper)	0 / 7	0 / 7	0 / 7	0 / 7
Noise US/DS	dB 5 / 6	dB 5 / 6	dB 5 / 6	dB 5 / 6
Output level CENELEC42 flat	dBμV 100	dBμV 98	dBμV 100	dBμV 101
Return way (KDG 1TS140)	dB medium load	dB medium load	dB medium load	dB medium load
Level adjustment US	dB 0 ... 20	dB 0 ... 20	dB 0 ... 20	dB 0 ... 20
Slope return way	dB -	dB -	dB 0 / 3 / 6 / 9	dB 0 / 3 / 6 / 9
Test point	-	-	Input+Output	Input+Output
Power supply	V~/W 230/7.5	V~/W 230/8	V~/W 230/8	V~/W 185-265/6
Dimensions / Weight	mm / kg 153 x 95 x 53 / 0.8	mm / kg 153 x 95 x 53 / 0.8	mm / kg 153 x 95 x 53 / 0.8	mm / kg 153 x 95 x 53 / 0.8
KDG class	B (1.1)	B (3.1)	B (3.2) + C (3.2)	C (4.2)

