


OPTICAL FIBRE PATCH CORD

- Excellent mechanical endurance and low insertion loss
- Standard exact plastic material, good exchangeability
- Cable diameter: Ø 3mm
- Single mode cable type SC, FC, LC, E2000/APC
- FTTx, Optical fibre CATV and test equipments



| Type | OMPC 015 SC-LC | OMPC 02 E2-FC | OMPC 02 SC-FC | OMPC 02 SC-SC |
|-------------|--------------------------------|---------------------------------|-----------------------------|------------------------------|
| Item No. | 57003185 | 57000920 | 57000922 | 57000923 |
| Description | SC/APC - LC/APC, 1.5 meters | E2000/APC - FC/APC, 2 meters | SC/APC - FC/PC, 2 meters | SC/APC - SC/APC, 2 meters |

| Type | OMPC 02 SC/APC-LC/PC | OMPC 02 LC/APC-LC/PC | OMPC 02 LC/PC-LC/PC |
|-------------|-----------------------------|-----------------------------|----------------------------|
| Item No. | 57004459 | 57004460 | 57004461 |
| Description | SC/APC - LC/PC, 2 meters | LC/APC - LC/PC, 2 meters | LC/PC - LC/PC, 2 meters |

| Type | OMPC 02 SC-LC | OMPC 02 LC-LC | OMPC 025 SC-LC | OMPC 05 SC-LC |
|-------------|------------------------------|------------------------------|--------------------------------|------------------------------|
| Item No. | 57002917 | 57002918 | 57003175 | 57003176 |
| Description | LC/APC - SC/APC, 2 meters | LC/APC - LC/APC, 2 meters | SC/APC - LC/APC, 2.5 meters | SC/APC - LC/APC, 5 meters |

| Type | OMPC 05 SC-SC | OMPC 10 SC-LC | OMPC 15 SC-LC | OMPC 20 SC-LC |
|-------------|------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Item No. | 57003210 | 57003431 | 57003432 | 57003433 |
| Description | SC/APC - SC/APC, 5 meters | SC/APC - LC/APC, 10 meters | SC/APC - LC/APC, 15 meters | SC/APC - LC/APC, 20 meters |

| Type | OMPC 15 SC-LC | OMPC 40 SC-FC | OMPC 40 SC-SC | OMPC 50 SC-FC | OMPC 100 SC-FC |
|-------------|--|---------------------------------------|--|---------------------------------------|--|
| Item No. | 57003656 | 57004241 | 57004226 | 57004293 | 57004240 |
| Description | SC/APC - LC/APC, 15 meters, armored | SC/APC - FC/PC, 40 meters, armored | SC/APC - SC/APC, 40 meters, armored | SC/APC - FC/PC, 50 meters, armored | SC/APC - FC/PC, 100 meters, armored |

| Type | OMPC 02 xx-yy | |
|-----------------------|---------------|-------------------------|
| Insertion loss | dB | < 0.2 |
| Return loss | dB | ≥ 45 |
| Mode-Operation | | Single mode, 9 / 125 µm |
| Type | | 8 ° APC |
| Operating temperature | °C | -40 - +75 |
| Storage temperature | °C | -40 - +85 |
| Length | m | up to 20 |