

## 17-CABLE COMPACT-MULTISWITCH - ACTIVE TERRESTRIAL PATH

Stand alone switch with power supply for 8-32 subscribers

- For 4 Sat positions
- Active Input for terrestrial and CATV signals without return way
- Metal housing with plastic side brackets
- Operating temperature range 0°C...+55°C
- Made in Germany



Type	MSE 1708 N		MSE 1712 N	
Item No.	57003326		57003327	
Frequency range	MHz	40...862   950...2400	40...862	950...2400
Inputs		1   16	1	16
Outputs receiver		8	12	
Gain	dB	0   -4...0	0	-4...0
Return loss trunk line	dB	> 10	> 10	
Isolation:	SAT/SAT	30	30	
	SAT/TER	30	30	
Output level:	35 dB IMA <sub>3</sub>	dBμV	105	105
	60 dB IMA <sub>3</sub>	dBμV	88	90
Operating voltage	V~	90...264	90...264	
Power supply LNB	mA	max. 1500	max. 1500	
Power consumption*	W	6.5	5.5	
Dimensions	mm	272 x 286 x 63	272 x 288 x 63	
Weight	kg	1.25	1.3	

\*without LNB remote feeding

Type	MSE 1716 N		MSE 1724 N		MSE 1732 N	
Item No.	57003328		57003329		57003330	
Frequency range	MHz	40...862   950...2400	40...862	950...2400	40...862	950...2400
Inputs		1   16	1	16	1	16
Outputs receiver		16	24		32	
Gain	dB	0   -4...0	0	-4...0	0	-4...0
Return loss trunk line	dB	> 10	> 10		> 10	
Isolation:	SAT/SAT	30	30		30	
	SAT/TER	30	30		30	
Output level:	35 dB IMA <sub>3</sub>	dBμV	105	105	105	
	60 dB IMA <sub>3</sub>	dBμV	90	90	90	
Operating voltage	V~	90...264	90...264		90...264	
Power supply LNB	mA	max. 1500	max. 1500		max. 1500	
Power consumption*	W	5.5	5.5		5.5	
Dimensions	mm	272 x 286 x 63	395 x 286 x 63		395 x 286 x 63	
Weight	kg	1.3	1.6		1.8	

\*without LNB