

17-CABLE COMPACT-MULTISWITCH - ACTIVE TERRESTRIAL PATH

Stand alone switch with power supply for 8-32 subscribers

- For 4 Sat positions
- Active Input for terrestrial and CATV signals without return way
- Metal housing with plastic side brackets
- Operating temperature range 0°C...+55°C
- Made in Germany



Type	MSE 1708 N		MSE 1712 N		
Item No.	57003326		57003327		
Frequency range	MHz	40...862	950...2400	40...862	950...2400
Inputs		1	16	1	16
Outputs receiver		8		12	
Gain	dB	0	-4...0	0	-4...0
Return loss trunk line	dB	> 10		> 10	
Isolation:	SAT/SAT	30		30	
	SAT/TER	30		30	
Output level:	35 dB IMA ₃	105		105	
	60 dB IMA ₃	88		90	
Operating voltage	V~	90...264		90...264	
Power supply LNB	mA	max. 1500		max. 1500	
Power consumption*	W	6.5		5.5	
Dimensions	mm	272 x 286 x 63		272 x 288 x 63	
Weight	kg	1.25		1.3	

*without LNB remote feeding

Type	MSE 1716 N		MSE 1724 N		MSE 1732 N		
Item No.	57003328		57003329		57003330		
Frequency range	MHz	40...862	950...2400	40...862	950...2400	40...862	950...2400
Inputs		1	16	1	16	1	16
Outputs receiver		16		24		32	
Gain	dB	0	-4...0	0	-4...0	0	-4...0
Return loss trunk line	dB	> 10		> 10		> 10	
Isolation:	SAT/SAT	30		30		30	
	SAT/TER	30		30		30	
Output level:	35 dB IMA ₃	105		105		105	
	60 dB IMA ₃	90		90		90	
Operating voltage	V~	90...264		90...264		90...264	
Power supply LNB	mA	max. 1500		max. 1500		max. 1500	
Power consumption*	W	5.5		5.5		5.5	
Dimensions	mm	272 x 286 x 63		395 x 286 x 63		395 x 286 x 63	
Weight	kg	1.3		1.6		1.8	

*without LNB