

## ACCESSOIRES

### Wideband - Quattro Adapter

- For conversion of a wideband LNB (L.O. 10,41 GHz) to conventional Quattro inputs
- Extension of existing installations from one into two satellite positions without new wiring
- Compact version
- Remote powered from Quattro Inputs



Type	WQA 24	
Item No.	57003355	
Inputs	2	
Input frequency	MHz	290...2340
Outputs	4	
Output frequency	MHz	950...2150
Conversion gain	dB	0
Input power	dBμV	54...84
Isolation	dB	26
Power consumption	mA	150 @ 20 V
Input voltage	VDC	10...20
Dimensions	mm	90 x 80 x 40

### Wideband Multi Splitter / Taps

- WBS splits the signal equally on both outputs
- WBT distributes a part of the signal to the outputs and attenuates the signal less than a splitter
- Low insertion loss
- DC power pass on all outputs



Type	WBS 2424		WBT 2424	
Item No.	57003450		57003451	
Frequency range SAT	MHz	290...2340	290...2340	
Frequency range TER	MHz	5...862	5...862	
Insertion loss	dB	5 (SAT)   4 (TER)	11 (SAT)   13 (TER)	
Through loss	dB	2 (SAT)   2 (TER)		
Tap loss	dB		13	
Return loss	dB	12		12
Dimensions	mm	129 x 129 x 51		129 x 129 x 51