

17-CABLE COMPACT-MULTISWITCH - PASSIVE TERRESTRIAL PATH

Stand alone switch with power supply for 8-32 subscribers

- For 4 Sat positions
- Input for terrestrial or CATV signals with return path
- Metal housing with plastic side brackets
- Operating temperature range 0°C...+55°C
- Made in Germany



Type		MSE 1708 NP		MSE 1712 NP	
Item No.		57003396		57003397	
Frequency range	MHz	5...862	950...2400	5...862	950...2400
Inputs		1	16	1	16
Outputs receiver		8		12	
Gain	dB	-22	-4...0	-27	-4...0
Return loss trunk line	dB	> 10		> 10	
Isolation:					
SAT/SAT	dB	30		30	
SAT/TER	dB	30		30	
Output level:			105		105
35 dB IMA ₃	dBμV	passive		passive	
60 dB IMA ₃	dBμV				
Operating voltage	V~	90...264		90...264	
Power supply LNB	mA	max. 1500		max. 1500	
Power consumption*	W	max. 1		max. 1	
Dimensions	mm	272 x 286 x 63		272 x 288 x 63	
Weight	kg	1.25		1.3	

*without LNB remote feeding

Type		MSE 1716 NP		MSE 1724 NP		MSE 1732 NP	
Item No.		57003398		57003399		57003400	
Frequency range	MHz	5...862	950...2400	5...862	950...2400	5...862	950...2400
Inputs		1	16	1	16	1	16
Outputs receiver		16		24		32	
Gain	dB	-27	-4...0	-33	-4...0	-33	-4...0
Return loss trunk line	dB	> 10		> 10		> 10	
Isolation:							
SAT/SAT	dB	30		30		30	
SAT/TER	dB	30		30		30	
Output level:			105		105		105
35 dB IMA ₃	dBμV	passive		passive		passive	
60 dB IMA ₃	dBμV						
Operating voltage	V~	90...264		90...264		90...264	
Power supply LNB	mA	max. 1500		max. 1500		max. 1500	
Power consumption*	W	max. 1.5		max. 2		max. 2.5	
Dimensions	mm	272 x 286 x 63		395 x 286 x 63		395 x 286 x 63	
Weight	kg	1.3		1.6		1.8	

*without LNB