


## OPTICAL FIBRE PATCH CORD

- Excellent mechanical endurance and low insertion loss
- Standard exact plastic material, good exchangeability
- Cable diameter: Ø 3mm
- Single mode cable type SC, FC, LC, E2000/APC
- FTTx, Optical fibre CATV and test equipments



Type	OMPC 015 SC-LC	OMPC 02 E2-FC	OMPC 02 SC-FC	OMPC 02 SC-SC
Item No.	57003185	57000920	57000922	57000923
Description	SC/APC - LC/APC, 1.5 meters	E2000/APC - FC/APC, 2 meters	SC/APC - FC/PC, 2 meters	SC/APC - SC/APC, 2 meters

Type	OMPC 02 SC/APC-LC/PC	OMPC 02 LC/APC-LC/PC	OMPC 02 LC/PC-LC/PC
Item No.	57004459	57004460	57004461
Description	SC/APC - LC/PC, 2 meters	LC/APC - LC/PC, 2 meters	LC/PC - LC/PC, 2 meters

Type	OMPC 02 SC-LC	OMPC 02 LC-LC	OMPC 025 SC-LC	OMPC 05 SC-LC
Item No.	57002917	57002918	57003175	57003176
Description	LC/APC - SC/APC, 2 meters	LC/APC - LC/APC, 2 meters	SC/APC - LC/APC, 2.5 meters	SC/APC - LC/APC, 5 meters

Type	OMPC 05 SC-SC	OMPC 10 SC-LC	OMPC 15 SC-LC	OMPC 20 SC-LC
Item No.	57003210	57003431	57003432	57003433
Description	SC/APC - SC/APC, 5 meters	SC/APC - LC/APC, 10 meters	SC/APC - LC/APC, 15 meters	SC/APC - LC/APC, 20 meters

Type	OMPC 15 SC-LC	OMPC 40 SC-FC	OMPC 40 SC-SC	OMPC 50 SC-FC	OMPC 100 SC-FC
Item No.	57003656	57004241	57004226	57004293	57004240
Description	SC/APC - LC/APC, 15 meters, armored	SC/APC - FC/PC, 40 meters, armored	SC/APC - SC/APC, 40 meters, armored	SC/APC - FC/PC, 50 meters, armored	SC/APC - FC/PC, 100 meters, armored

Type	OMPC 02 xx-yy	
Insertion loss	dB	< 0.2
Return loss	dB	≥ 45
Mode-Operation		Single mode, 9 / 125 μm
Type		8 ° APC
Operating temperature	°C	-40 - +75
Storage temperature	°C	-40 - +85
Length	m	up to 20