

## OPTICAL QUATTRO FINAL UNIT

- || Excellent optical sensitivity
- || Powered via RF outputs or separate power supply (NT 20-1.2F Item No. 57004430)
- || LED indication of optical signal & power supply



Type		OQC 34	OQC 34-2	
Item-No.		57004462	57004463	
Optical	Wavelengths	nm	1310, 1330, 1550	
	Inputs		1	
	Connector Type		SC / APC	
	Optical Input Level	dBm	-14 ... 0	
Terrestrial	Frequency Range	MHz	40...790	
	Outputs (Trunk)		1 (F-Type)	
	Output Level (AGC)	dBμV	Quattro 65	
Sat	F Frequency Range	MHz	950...2150	
	Outputs (Trunk)		4 (F-Typ)	
	Output Level	dBμV	Quattro: 80 (AGC)	
In General	DC Powering	Can be powered from the DC jack or from the SAT RF outputs (all F-type)		
	Operation Indication	Green LED (front bottom left)		
	Voltage	10 to 20 VDC from connected receivers or multiswitches, 11 to 20 VDC from power supply		
	Max. Power Consumption	W	8	
	DC via RF outputs		Yes (not on the terrestrial HF output)	
	Shortage & Power On Diagnostics		Yes	
	Earth Connector		1	
	Operation Temperature Range	°C	-20...+50°C (for indoor mounting only)	
	Dimensions	mm	164 x 142 x 50	
	Weight	kg	0.48	