


ATTENUATION JXP-PADS

- Fix attenuation-PAD's
- 1 dB step values for gain and slope adjustment
- Plastic cover for solid protection
- Length 1" available



| Type | PAD 0 | PAD 1 | PAD 2 | PAD 3 | PAD 4 | PAD 5 | PAD 6 |
|----------|----------|----------|----------|----------|----------|----------|----------|
| Item No. | 10161523 | 10161524 | 10161525 | 10161526 | 10161527 | 10161528 | 10161529 |
| Loss dB | 0 | 1 | 2 | 3 | 4 | 5 | 6 |
| Type | PAD 7 | PAD 8 | PAD 9 | PAD 10 | PAD 11 | PAD 12 | PAD 13 |
| Item No. | 10161530 | 10161531 | 10161532 | 10161533 | 10161534 | 10161535 | 10161536 |
| Loss dB | 7 | 8 | 9 | 10 | 11 | 12 | 13 |
| Type | PAD 14 | PAD 15 | PAD 16 | PAD 17 | PAD 18 | PAD 19 | PAD 20 |
| Item No. | 10161537 | 10161538 | 10161539 | 10161540 | 10161541 | 10161542 | 10161543 |
| Loss dB | 14 | 15 | 16 | 17 | 18 | 19 | 20 |

Length 25.4 mm (1")

PAD SETBOX



| Type | pre equipped | unequipped |
|-------------|---|----------------------------------|
| Item No. | 57002032 | 57002084 |
| Description | Setbox equipped with 630 pcs PADs 30 x 0, 1, 2 ... 20 dB PADs 1" | Empty setbox with 21 separations |

CABLE SIMULATOR PADS

- Frequency range 47-1218 MHz
- 5.6 mm thick

| Type | CSP 12045 | CSP 12060 | CSP 12075 | CSP 12090 | CSP 12105 |
|---------------------------|------------------|------------------|------------------|------------------|------------------|
| Item No. | 57003641 (PU 10) | 57003642 (PU 10) | 57003643 (PU 10) | 57003644 (PU 10) | 57003645 (PU 10) |
| EQ values db | 4.5 | 6.0 | 7.5 | 9.0 | 10.5 |
| 47 - 1218 MHz db | 3.7 | 4.9 | 6.2 | 7.4 | 8.6 |
| 47 - 1000 MHz db | 3.2 | 4.3 | 5.4 | 6.4 | 7.5 |
| 47 - 870 MHz db | 2.9 | 3.9 | 4.8 | 5.8 | 6.8 |
| Tolerance eq-val. max. db | +/- 0.5 | | | | |
| Flatness db | +/- 0.2 | | | | |
| Insertion loss db | ≤ 1 | | | | |
| Return loss db | ≥ 1 | | | | |
| Impedance Ω | 75 | | | | |

Length 25.4 mm (1")