


GALVANIC ISOLATOR

- || To avoid offset current between different electrical potentials
- || Capacitors for galvanic isolation of IN- and outputs
- || Surge- and Burstprotection up to 2 kV
- || No DELTA labelling



Type		TRIS-1002 AEN
Item No.		10161670
Frequency range	MHz	5-1000
Through loss	dB	0.5 ... 1.0
Linearity	dB	± 0.5
Proof Voltage	kV	2 (between in- and output potentials)
Dimensions W x L x D	mm	60 x 30 x 38

TRIS-1002 HOUSING

- || TRIS-1002 housing for the galvanic isolator
- || Suitable for TRIS-1002 AEN (10161670)



Type		TRIS-1002 Housing
Item No.		57001201
Dimensions	mm	85 x 85 x 40

FIX ATTENUATOR

- || Small housing, 40 x Ø 11 mm
- || Connector: F-female and F-male
- || CLASS A



KLASSE
A
CLASS

Type	FR 3-3	FR 3-6	FR 3-10
Item No.	57001154	57001155	57001156
Frequency range	MHz	5 - 2400	5 - 2400
Attenuation	dB	3	6
Remarks	DC-Pass	DC-Pass	DC-Pass

Type	FR 1-3	FR 1-6	FR 1-10
Item No.	57002351	57002352	57002353
Frequency range	MHz	5 - 1000	5 - 1000
Attenuation	dB	3	6