


AMPLIFIER

- II Two trunk lines
- II Remote or direct powered *
- II Separate adjustment of gain and slope for each input



Type		WBV 230
Item No.		57003181
Inputs SAT		2
Frequency range SAT	MHz	290...2340
Outputs trunk line		2
Output level	dBμV	110
Gain	dB	30
Gain adjustment range	dB	15...30
Equalizer adjustment range	dB	0...15
Power consumption	mA	150 @ 20 V
Dimensions	mm	129 x 114 x 51

* Power supply from externally. It can be driven with an external plug-in power supply (e.g. NG 1212; Item-No. 57002648) or by remote feeding through trunk lines.

ACCESSORIES

Wideband - Quattro Adapter

- II For conversion of a wideband LNB to conventional Quattro inputs
- II Extension of existing installations from one into two satellite positions without new wiring
- II Compact version
- II Remote powered from Quattro Inputs



Type		WQA 24
Item No.		57003355
Inputs		2
Input frequency	MHz	290...2340
Outputs		4
Output frequency	MHz	950...2150
Conversion gain	dB	0
Input power	dBμV	54...84
Isolation	dB	26
Power consumption	mA	150 @ 20 V
Input voltage	VDC	10...20
Dimensions	mm	90 x 80 x 40